

AW 705 - Tekniska specifikationer



Description

AW 705 har utvecklats för arbetsfordon, släpvagnar och balpressar inom jordbearbetning och transportarbeten. Det är idealiskt för det moderna lantbruket tack vare förbättrad hållbarhet och hög lastkapacitet.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn

Version	SPECIAL
Type	TL
Tyre Size	16.0/70 - 20
LI/SS FREE ROLLING	154 A8

Dimensions US Standard

Usa code	94029884
Ply Rating	14
Section Width (inch)	16.1
Overall Diameter (inch)	42.3
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	124.2
Rim Rec	13.0
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E11-106R-004252

Load capacity (lbs)

mph / psi	51
5 FR	11570
15 FR	9840
20 FR	9260
25 FR	8270

Printed on 4/25/2024 8:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..