

## AW 708 IND - Tekniska specifikationer



### Description

AW 708 IND har utvecklats för industriella släpvagnar. En HD-version med en speciell skär- och flisbeständig sammansättning finns tillgänglig.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Släpvagn

Version	INDUSTRIAL
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Section Width (mm)</b>	405
<b>Overall Diameter (mm)</b>	875
<b>Static Loaded Radius (mm)</b>	380
<b>Rolling Circumference (mm)</b>	2564
<b>Rim Rec</b>	AG 13.00
<b>ECE</b>	E11-106R-004254

## Load capacity (Kg)

	km/h / bar	4.50
	10 FR	4550
	25 FR	3870
	30 FR	3640
	40 FR	3250

Printed on 4/17/2024 6:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..