



AW 708 IND - Ladda ned faktablad



Description

AW 708 IND har utvecklats för industriella släpvagnar. En HD-version med en speciell skär- och flisbeständig sammansättning finns tillgänglig.

UM

International Standard

Construction

❖ BIAS

Machinery

Industri: Släpvagn

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	INDUSTRIAL	149 A8	18	AG 13.00		405	875	380	2564	TL	E11-106R-004254

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 12:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..