

AW 708 - Tekniska specifikationer

Description

AW 708 har utvecklats för jordbearbetning, transporter och höskördning med arbetsfordon, släp och balpressar. Det finns även en "HD"-version i en speciell gummiblandning med extra motståndskraft mot skärande underlag och punkteringar.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn
Industri: Släpvagn



Version	STUBBLE RESISTANT
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	152 A8

Dimensions International Standard

Ply Rating	22
Section Width (mm)	470
Overall Diameter (mm)	866
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2536
Rim Rec	16.00
ECE	E11-106R-003636

Load capacity (Kg)

	km/h / bar	3.90
	10 FR	4970
	25 FR	4225
	30 FR	3975
	40 FR	3550

Printed on 4/23/2024 12:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..