

## AW 708 - Tekniska specifikationer

### Description

AW 708 har utvecklats för jordbearbetning, transporter och höskördning med arbetsfordon, släp och balpressar. Det finns även en "HD"-version i en speciell gummiblandning med extra motståndskraft mot skärande underlag och punkteringar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn  
Industri: Släpvagn



Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	138 A8

## Dimensions International Standard

<b>Ply Rating</b>	10
<b>Section Width (mm)</b>	470
<b>Overall Diameter (mm)</b>	866
<b>Static Loaded Radius (mm)</b>	380
<b>Rolling Circumference (mm)</b>	2536
<b>Rim Rec</b>	16.00
<b>ECE</b>	E4-106R-002334

## Load capacity (Kg)

	km/h / bar	2.25
	10 FR	3305
	25 FR	2810
	30 FR	2645
	40 FR	2360

Printed on 4/20/2024 5:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..