

AW 708 - Tekniska specifikationer



Description

AW 708 har utvecklats för jordbearbetning, transporter och höskördning med arbetsfordon, släp och balpressar. Det finns även en "HD"-version i en speciell gummiblandning med extra motståndskraft mot skärande underlag och punkteringar.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn
Industri: Släpvagn

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS FREE ROLLING	140 A8

Dimensions US Standard

Usa code	94010363
Ply Rating	10
Section Width (inch)	19.7
Overall Diameter (inch)	37.2
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	108.3
Rim Rec	16.00
ECE	E4-106R-001884

Load capacity (lbs)

mph / psi	29
5 FR	7720
15 FR	6560
20 FR	6170
25 FR	5510

Printed on 4/23/2024 3:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..