AW 711 - Tekniska specifikationer

Description

AW 711 är ett radialdäck specialkonstruerat för modernt lantbruk, och lämpar sig för transporter, höskördning och jordbearbetning. Tack vare den speciella gummiblandningen har AW 711 utökad livslängd, oavsett om det körs på mjukt eller hårt underlag. Det låga rullmotståndet vid vägkörning leder till betydande besparingar i bränsleförbrukning. Tack vare VF-teknologin har AW 711 hög lastkapacitet vid lågt ringtryck.

UM

US Standard

Construction

RADIAL

Machinery

Lantbruk: Höskördemaskin • Arbetsfordon

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	395/55 R 16.5
LI/SS	152 A8/B

Dimensions US Standard

Usa code	94053469
Section Width (inch)	15.5
Overall Diameter (inch)	33
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	99.1
Rim Rec	12
ECE	E11-106R-002997

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
30	2350	3050	3760	4310	5020	5720	6110	6730	7360	7830
25	2350	3050	3760	4310	5020	5720	6110	6730	7360	7830
20	2630	3430	4220	4830	5620	6420	6840	7550	8260	8770
15	2800	3640	4480	5130	5960	6800	7270	8010	8760	9310
10	2970	3860	4740	5430	6320	7210	7700	8490	9280	9870
5	3300	4280	5270	6030	7020	8000	8550	9420	10310	10960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 8:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..