

AW 711 - Tekniska specifikationer



Description

AW 711 är ett radialdäck specialkonstruerat för modernt lantbruk, och lämpar sig för transporter, höskördning och jordbearbetning. Tack vare den speciella gummiblandningen har AW 711 utökad livslängd, oavsett om det körs på mjukt eller hårt underlag. Det låga rullmotståndet vid vägkörning leder till betydande besparingar i bränsleförbrukning. Tack vare VF-teknologin har AW 711 hög lastkapacitet vid lågt ringtryck.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Höskördemaskin • Arbetsfordon

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	400/60 R 18
LI/SS	159 A8/B

Dimensions International Standard

Section Width (mm)	394
Overall Diameter (mm)	945
Static Loaded Radius (mm)	419
Rolling Circumference (mm)	2807
SRI (mm)	450
Rim Rec	14
Rim Alt	13
ECE	E4-106R-001397

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	3.8	4.0	5.0	5.5
50	1220	1585	1950	2235	2600	2965	3165	3490	3655	3815	4057	4375
40	1220	1585	1950	2235	2600	2965	3165	3490	3655	3815	4057	4375
30	1365	1775	2185	2500	2910	3320	3550	3910	4095	4275	4545	4900
25	1450	1885	2320	2660	3095	3530	3770	4155	4350	4545	4830	5210
20	1535	1995	2460	2815	3275	3735	3990	4400	4605	4810	5115	5515
10	1705	2220	2730	3125	3640	4150	4435	4885	5115	5340	5680	6125

Printed on 11/30/2023 5:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..