AW 711 - Tekniska specifikationer

Description

AW 711 är ett radialdäck specialkonstruerat för modernt lantbruk, och lämpar sig för transporter, höskördning och jordbearbetning. Tack vare den speciella gummiblandningen har AW 711 utökad livslängd, oavsett om det körs på mjukt eller hårt underlag. Det låga rullmotståndet vid vägkörning leder till betydande besparingar i bränsleförbrukning. Tack vare VF-teknologin har AW 711 hög lastkapacitet vid lågt ringtryck.

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Höskördemaskin • Arbetsfordon

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 340/65 R 18
LI/SS	153 A8/B

Dimensions International Standard

Section Width (mm)	330
Overall Diameter (mm)	899
Static Loaded Radius (mm)	381
Rolling Circumference (mm)	2703
SRI (mm)	450
Rim Rec	W 11
ECE	E11-106R-002992

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
From 10 to 50 km/h	1170	1535	1865	2155	2485	2815	3030	3325	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 9:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..