# AW 711 - Tekniska specifikationer

## Description

AW 711 är ett radialdäck specialkonstruerat för modernt lantbruk, och lämpar sig för transporter, höskördning och jordbearbetning. Tack vare den speciella gummiblandningen har AW 711 utökad livslängd, oavsett om det körs på mjukt eller hårt underlag. Det låga rullmotståndet vid vägkörning leder till betydande besparingar i bränsleförbrukning. Tack vare VF-teknologin har AW 711 hög lastkapacitet vid lågt ringtryck.

## UM

US Standard

## Construction

RADIAL

## Machinery

Lantbruk: Höskördemaskin • Arbetsfordon

| | |
|---|---|
| **Version** | STEEL BELTED |
| **Type** | TL |
| **Tyre Size** | VF 410/50 R 16.5 |
| **LI/SS** | 153 B |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94055814 |
| **Section Width (inch)** | 16.1 |
| **Overall Diameter (inch)** | 32.9 |
| **Static Loaded Radius (inch)** | 13.8 |
| **Rolling Circumference (inch)** | 98.9 |
| **Rim Rec** | AG 11.75 |
| **ECE** | E11-106R-005024 |

## Load capacity (lbs)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 67 |
|---|---|---|---|---|---|---|---|---|---|---|
| From 5 to 30 mph | 2260 | 2970 | 3590 | 4170 | 4790 | 5430 | 5850 | 6420 | 7040 | 8050 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..