AW 726 - Tekniska specifikationer

Description

AW 726 har konstruerats särskilt för släp till transportarbeten. Det lämpar sig för både väg- och terrängkörning. AW 726 ger utmärkt prestanda på vägen och besitter självrensande egenskaper. Blockmönstret förlänger däckets livslängd.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Släpvagn

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	400
Overall Diameter (mm)	875
Rim Rec	AG 13.00
ECE	E11-106R-005341

Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..