

## AW 726 - Ladda ned faktablad

### Description

AW 726 har konstruerats särskilt för släp till transportarbeten. Det lämpar sig för både väg- och terrängkörning. AW 726 ger utmärkt prestanda på vägen och besitter självrensande egenskaper. Blockmönstret förlänger däckets livslängd.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Släpvagn



SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11.5/80 - 15.3	ARAMID BELTED	126 A8	139 A8	14	9.00		300	855	363	2531	TL	
11.5/80 - 15.3	STANDARD	126 A8	139 A8	14	9.00		300	855	363	2531	TL	E11-106R-005264
11.5/80 - 15.3	STEEL BELTED	126 A8	139 A8	14	9.00		300	855	373	2540	TL	E11-106R-006974
400/60 - 15.5	STANDARD	137 A8	149 A8	18	AG 13.00		400	875	0	0	TL	E11-106R-005341
420/55 - 17	STANDARD	121 A8	133 A8		13.00		415	890	392	2584	TL	E11-106R-005265

Printed on 4/24/2024 5:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..