

## AW 729 - Tekniska specifikationer



### Description

AW 729 är ett specialdesignat lantbruksdäck för transporter, höskördning, balning och jordbearbetning. Den rundade däcksuldran och däkmönstret med tre mittspår ger minskad jordpackning och förebygger markskador.

AW 729 är ett utmärkt däck för det moderna lantbruket och lämpar sig väl för användning både på väg och i terräng.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

## Dimensions International Standard

Section Width (mm)	500
Overall Diameter (mm)	945
Static Loaded Radius (mm)	426
Rolling Circumference (mm)	2885
Rim Rec	16.00
ECE	E11-106R-006616

## Load capacity (Kg)

	km/h / bar	2.80
	10 FR	4550
	25 FR	3870
	30 FR	3640
	40 FR	3250
	10 DW	3220
	25 DW	2735
	30 DW	2575
	40 DW	2300

Printed on 4/25/2024 11:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..