

## AW 909 - Tekniska specifikationer



### Description

AW 909 har utvecklats för jordbearbetning, höskördning och transporter med arbetsfordon, släp och balpressar. Det är idealiskt för det moderna lantbruket och kan köras både på väg och i terräng.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	11.5/80 - 15.3
LI/SS FREE ROLLING	141 A8

## Dimensions US Standard

Usa code	94010660
Ply Rating	16
Section Width (inch)	11.8
Overall Diameter (inch)	33.2
Static Loaded Radius (inch)	14.6
Rolling Circumference (inch)	97.4
Rim Rec	9.00
ECE	E4-106R-002752

## Load capacity (lbs)

mph / psi	78
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680

Printed on 4/23/2024 1:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..