

AW 909 - Tekniska specifikationer



Description

AW 909 har utvecklats för jordbearbetning, höskördning och transporter med arbetsfordon, släp och balpressar. Det är idealiskt för det moderna lantbruket och kan köras både på väg och i terräng.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	134 A8

Dimensions US Standard

Usa code	94010752
Ply Rating	10
Section Width (inch)	15.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98
Rim Rec	13.00
Rim Alt	13
ECE	E4-106R-001546

Load capacity (lbs)

mph / psi	38
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Printed on 4/25/2024 9:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..