

BK 308 - Tekniska specifikationer



Description

BK 308 är ett däck för släpvagnar och kompaktraktorer. Det har utmärkt dragkraft på alla ytor och ett mönster som minskar mängden sprickor i spåren. Det kraftiga höljet ger en utmärkt hållbarhet och skydd mot punkteringar, och den speciella gummiblandningen i slitbanan ger däckets en lång livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Kompaktraktor • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	104 A8

Dimensions US Standard

Usa code	94044993
Ply Rating	10
Section Width (inch)	7.5
Overall Diameter (inch)	34.1
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-003563

Load capacity (lbs)

mph / psi	70
25	1985

Printed on 4/26/2024 10:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..