

BK 826 - Tekniska specifikationer



Description

BK 826 har specialkonstruerats för släp vid transportarbeten. Det är ett diagonaldäck med utmärkt hög lastkapacitet tack vare dess förstärkta däckstomme. BK 826 finns även tillgängligt i en industriversion som har extra motståndskraft mot skärande underlag och punkteringar och är även lämpligt för grävlastare.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Släpvagn

Industri: Grävlastare • Släpvagn

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

Dimensions International Standard

Ply Rating	14
Section Width (mm)	238
Overall Diameter (mm)	863
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E4-54R-0024095

Load capacity (Kg)

km/h / bar	6.90
100 LS	1745
100 LD	1650

Printed on 4/25/2024 11:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..