

BK-LOADER 53 - Tekniska specifikationer



Description

BK-LOADER 53 har aramidbälte och passar hjullastare som används för industriändamål. Den unika mönsterdesignen och det extra djupa mönstret ger bästa möjliga stabilitet i sidled, en slitbana med längre livslängd och ett utomordentligt skydd mot skärskador och punkteringar. BK-LOADER 53 har utomordentliga självrensande egenskaper samt utmärkt grepp och dragkraft på både våta och torra underlag. Det här däckets passar utmärkt för återvinningsarbete.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Hjullastare

Version	ARAMID BELTED
Type	TL
Tyre Size	405/70 R 18
LI/SS	153A2/149A4

Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1045
Rim Rec	13
Rim Alt	14 ; 13 SDC; 12 ;12 SDC

Load capacity (Kg)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
20 TRANSPORT	1140	1465	1725	1985	2275	2505	2765	2990	3250
10 LOADING	1280	1645	1935	2230	2555	2815	3105	3360	3650
STATIC	2050	2635	3105	3570	4095	4505	4975	5385	5850

Printed on 4/13/2024 12:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..