

## BOGMAX - Tekniska specifikationer



### Description

BOGMAX är särskilt konstruerat för terrängkörning. Mönstret är extra djupt och ger utmärkt dragförmåga, samtidigt som skydd i sidoväggen motverkar stötar och risken för skador. BOGMAX är ett däck med sex skikt och M+S-teknologi – perfekt till terrängsport under alla förhållanden.

### UM

International Standard

### Construction

BIAS

### Machinery

Lantbruk: Fyrhjuling

Version	STANDARD
Type	TL
Tyre Size	AT 30 X 10 - 14
LI/SS	58 F

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	260
Overall Diameter (mm)	760
Rim Rec	7.0 AT
Rim Alt	7.5 AT ; 8.0 AT

## Load capacity (Kg)

km/h / bar	0.50
80	236

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 3:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..