COMMANDER 3 RIB - Tekniska specifikationer

Description

COMMANDER 3 RIB är ett framdäck med tre mönsterribbor konstruerat för jordbearbetning och transportarbeten. Det erbjuder utmärkt hållbarhet och lastkapacitet, tack vare den optimerade viktfördelningen och ribbad däckskuldra. Det starka däckhöljet med en gummiblandning för hög motståndskraft mot skärande underlag är en garanti för enastående skydd mot punkteringar.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Tvåhjulsdriven traktor

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	175
Overall Diameter (mm)	740
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004415
TRA Code	F2

Load capacity (Kg)

km/h / bar	4.50
30	670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 11:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..