

## COMMANDER (F) - Tekniska specifikationer



### Description

COMMANDER (F) är ett framdäck med tre mönsterribbor – perfekt till jordbearbetning och transportarbeten. Det djupa mönstret är tillverkat i en gummblandning med utmärkt motståndskraft mot skärande underlag och punkteringar, vilket ger längre livslängd och hög lastkapacitet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Tvåhjulsdreven traktor

Version	STANDARD
Type	TT
Tyre Size	5.50 - 16
LI/SS	78 A8

## Dimensions US Standard

Usa code	94052806
Ply Rating	6
TMPH	1
Section Width (inch)	6.1
Overall Diameter (inch)	28.3
Static Loaded Radius (inch)	13.4
Rolling Circumference (inch)	84.4
Rim Rec	4.00 E
Rim Alt	3.50D ; 4.50E
ECE	E11-106R-003308
TRA Code	F2

## Load capacity (lbs)

mph / psi	56
25	937

Printed on 4/19/2024 10:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..