

COMMANDER (F) - Ladda ned faktablad



Description

COMMANDER (F) är ett framdäck med tre mönsterribbor – perfekt till jordbearbetning och transportarbeten. Det djupa mönstret är tillverkat i en gummblandning med utmärkt motståndskraft mot skärande underlag och punkteringar, vilket ger längre livslängd och hög lastkapacitet.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Tvåhjuldriven traktor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TKPH	ECE
5.50 - 16	STANDARD	F2	86 A6	6	4.00 E	3.50D ; 4.50E	155	720	340	2145	TT	1	E11-106R-003308
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5.00 F	175	750	357	2308	TT	0	E11-106R-003001
6.50 - 16	STANDARD	F2	102 A6	10	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	770	362	2332	TT	1	E11-106R-004109
6.50 - 16	STANDARD	F2	98 A6	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	183	770	362	2332	TT	1	E11-106R-004107
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	210	810	381	2477	TT	1	E11-106R-004116

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/29/2025 6:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..