

## COMMANDER (R) - Tekniska specifikationer



### Description

COMMANDER (R) är ett lantbruksdäck med djupt mönster och robusta däckklackar för längre livslängd. Den speciella däckklacksdesignen med dubbla vinklar ger utmärkt dragförmåga på åkern och förstklassiga självrensande egenskaper. Det robusta däckhöljet är tillverkat i en gummiblandning med stor motståndskraft mot skärande underlag och punkteringar samt hög lastkapacitet. COMMANDER (R) är det perfekta däck till jordbearbetning, transport- och skördarbeten.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Skördemaskin • Traktor

Version	STANDARD
Type	TT
Tyre Size	11.2 - 24
LI/SS	123 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	295
Overall Diameter (mm)	1125
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3483
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004616
TRA Code	R1

## Load capacity (Kg)

km/h / bar	3.6
30	1550

Printed on 4/27/2024 4:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..