

## COMMANDER (R) - Tekniska specifikationer



### Description

COMMANDER (R) är ett lantbruksdäck med djupt mönster och robusta däckklackar för längre livslängd. Den speciella däckklacksdesignen med dubbla vinklar ger utmärkt dragförmåga på åkern och förstklassiga självrensande egenskaper. Det robusta däckhöljet är tillverkat i en gummiblandning med stor motståndskraft mot skärande underlag och punkteringar samt hög lastkapacitet. COMMANDER (R) är det perfekta däck till jordbearbetning, transport- och skördarbeten.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Skördemaskin • Traktor

Version	STANDARD
Type	TT
Tyre Size	17.9 - 28
LI/SS	140 A8

## Dimensions US Standard

Usa code	94073214
Ply Rating	12
TMPH	1
Section Width (inch)	18
Overall Diameter (inch)	59.6
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-007701
TRA Code	R1

## Load capacity (lbs)

mph / psi	32
25	5520

Printed on 4/27/2024 12:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..