

COMMANDER TWIN RIB - Tekniska specifikationer



Description

COMMANDER TWIN RIB är ett däck med fyra mönsterribbor och skulderhack för utmärkt grepp. Den breda mönsterprofilen ger god viktfördelning. Det kraftfulla däckhöljet med överlägsen gummiblandning ger längre livslängd till däck. COMMANDER TWIN RIB är perfekt till jordbearbetning och transportarbeten.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Tvåhjuldriven traktor

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	98 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	180
Overall Diameter (mm)	761
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E11-106R-004107
TRA Code	F2

Load capacity (Kg)

km/h / bar	4.20
30	750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 3:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..