CON STAR - Tekniska specifikationer

Description

CON STAR lämpar sig särskilt för kompakthjullastare och teleskoplastare inom industriellt lantbruk, lyft- och lastarbeten. Däcket erbjuder utmärkt dragförmåga samt mycket hög vertikal och lateral stabilitet. CON STAR är tillverkat i en gummiblandning som ger motståndskraft mot skärande underlag och punkteringar och bidrar till längre livslängd.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Kompakthjullastare • Teleskoplastare
Industri: Kompakthjullastare • Teleskoplastare

Version	INDUSTRIAL
Type	TL
Tyre Size	400/70 - 20 (16.0/70 - 20)
LI/SS	149 A8

Dimensions US Standard

Usa code	94043323
Ply Rating	16
Section Width (inch)	15.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	130
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E11-106R-003024

Load capacity (lbs)

mph / psi	58
25	7150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 5:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..