CONTAINER KING - Tekniska specifikationer

Description

CONTAINER KING är konstruerat för reachstackers inom intermodala transporter och logistiktillämpningar. Det här enastående däcket är tillverkat i en extra slitstark gummiblandning som minimerar sprickor i slitbanan. CONTAINER KING säkerställer lång livslängd samt enastående stabilitet under lyftarbeten.

UM

US Standard

Construction

BIAS

Machinery

Industri: Reachstacker

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94069798
Ply Rating	24
Overall Width (inch)	13
Overall Diameter (inch)	50.6
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	22650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 8:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..