

CRANE SPECIAL - Tekniska specifikationer



Description

CRANE SPECIAL är ett däck för pick and carry-kranar i tuff terräng. Däcket är tillverkat av en speciell gummiblandning som ger hög stabilitet och pålitlighet.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Kranbil

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 14.00 - 24 |

Dimensions International Standard

| | |
|----------------------------|---------|
| Ply Rating | 24 |
| Overall Width (mm) | 375 |
| Overall Diameter (mm) | 1368 |
| Static Loaded Radius (mm) | 628 |
| Rolling Circumference (mm) | 4050 |
| Rim Rec | 10.00 W |
| TRA Code | E3 |

Load capacity (Kg)

| km/h / bar | 5.75 |
|------------|------|
| 50 | 5150 |

Printed on 4/25/2024 11:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..