

DESERT KING - Tekniska specifikationer



Description

DESERT KING passar bäst för löst underlag, sandig terräng och gatstenstillämpningar med ökenlastbilar. Den optimerade designen av däckribbor ger utmärkt flyt och riktningsstabilitet. Dess starka nylonhölje och tunga däckvulst är speciellt utvecklade för lågtrycksoperationer. DESERT KING ger också en hög motståndskraft mot punkteringar och en längre däcklivslängd.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Ökenlastbil

Version	STANDARD
Type	TL
Tyre Size	21.00 - 25 DT

Dimensions International Standard

Ply Rating	16
Section Width (mm)	570
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4906
Rim Rec	15.00/3.0
TRA Code	E7
Tread Depth	18

Load capacity (Kg)

km/h / bar	2.50
10	9750
50	6700
65	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..