

DESERT KING - Ladda ned faktablad



Description

DESERT KING passar bäst för löst underlag, sandig terräng och gatstenstillämpningar med ökenlastbilar. Den optimerade designen av däckribbor ger utmärkt flyt och riktningsstabilitet. Dess starka nylonhölje och tunga däckvulst är speciellt utvecklade för lågtrycksoperationer. DESERT KING ger också en hög motståndskraft mot punkteringar och en längre däcklivslängd.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Ökenlastbil

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	Tread Depth
18.00 - 25 DT	STANDARD	94069743	E7	16	10.00/1.5		18.5	60.4	25	173.4	TL	20
21.00 - 25 DT	STANDARD	94067633	E7	16	15.00/3.0		22.4	65.4	27.9	193.1	TL	22
29.5 - 25 DT	STANDARD	94069057	E7	28	25.00/3.5		30.3	71.7	30.9	212.3	TL	26

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..