

EARTHMAX SR 22 AS - Tekniska specifikationer



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) är ett stålradialdäck speciellt utformat för att användas på snö och is och säkerställer optimala prestanda under alla årstider.

Däcket har ett unikt däckmönster med djupa mönsterkanaler och har en sammansättning speciellt framtagen för vinterförhållanden som ger överlägsna bromsegenskaper på is och snö, och förhindrar att stenar fastnar i mönstret under hela året.

EARTHMAX SR 22 AS har en låg blocktäthet och ett brett avtryck som ger utmärkt dragförmåga och stabilitet med jämnt slitage och lång livslängd.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Väghyvlare • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/153 A8/182 A2

Dimensions International Standard

Overall Width (mm)	445
Overall Diameter (mm)	1350
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	4010
Rim Rec	14.00/1.5
Star Rating	**/*/**
TRA Code	E2/G2/L2
Tread Depth	28

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	-	-	-	-	-	-	-	-	4375	4625	4750	5000	5150	5450	-	-	-	-	-
40	1850	2120	2360	2650	2900	3075	03350	3650	-	-	-	-	-	-	-	-	-	-	-
10	-	-	-	-	-	-	-	-	-	-	-	-	-	7300	7500	7750	8000	8250	8500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 00:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..