

EARTHMAX SR 22 AS - Tekniska specifikationer



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) är ett stålradialdäck speciellt utformat för att användas på snö och is och säkerställer optimala prestanda under alla årstider.

Däcket har ett unikt däckmönster med djupa mönsterkanaler och har en sammansättning speciellt framtagen för vinterförhållanden som ger överlägsna bromsegenskaper på is och snö, och förhindrar att stenar fastnar i mönstret under hela året.

EARTHMAX SR 22 AS har en låg blocktäthet och ett brett avtryck som ger utmärkt dragförmåga och stabilitet med jämnt slitage och lång livslängd.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Väghyvlare • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/161 A8/193 A2

Dimensions US Standard

Usa code	94073160
Overall Width (inch)	20.9
Overall Diameter (inch)	58.8
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	170.2
Rim Rec	17.00/2.0
Star Rating	**/**/**
TRA Code	E2/G2/L2
Tread Depth	40

Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91	94
30	-	-	-	-	-	-	-	-	12800	13600	14300	14800	15200	16100	-	-	-	-	-
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	21500	22000	22700	24000	24700	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 1:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..