

EARTHMAX SR 22 AS - Ladda ned faktablad



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) är ett stålradialdäck speciellt utformat för att användas på snö och is och säkerställer optimala prestanda under alla årstider.

Däcket har ett unikt däckmönster med djupa mönsterkanaler och har en sammansättning speciellt framtagen för vinterförhållanden som ger överlägsna bromsegenskaper på is och snö, och förhindrar att stenar fastnar i mönstret under hela året.

EARTHMAX SR 22 AS har en låg blocktätthet och ett brett avtryck som ger utmärkt dragförmåga och stabilitet med jämnt slitage och lång livslängd.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Väghyvlare • Hjullastare

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
14.00 R 24	CUT RESISTANT COMPOUND	94075201	G2/L2	*	153 A8/175 A2	8.00 TG	9.00 GR , 10.00 VA	15.4	53.9	24.6	163	TL	32
17.5 R 25	CUT RESISTANT COMPOUND	94069613	E2/G2/L2	**/*/**	167 B/153 A8/182 A2	14.00/1.5		17.5	53.1	23.4	157.9	TL	35
20.5 R 25	CUT RESISTANT COMPOUND	94073160	E2/G2/L2	**/*/**	177 B/161 A8/193 A2	17.00/2.0		20.9	58.8	25.2	170.2	TL	40
23.5 R 25	CUT RESISTANT COMPOUND	94073405	E2/G2/L2	**/*/**	185 B/170 A8 /201 A2	19.50/2.5		24	63.5	27.9	191.5	TL	42

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 20:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..