

EARTHMAX SR 22 - Tekniska specifikationer



Description

EARTHMAX SR 22 (G-2/L-2) är ett stålradialdäck särskilt avsett för väghyvlar och hjullastare som används på is och snö under extrema vinterförhållanden. Förarna uppskattar det grova symmetriska slitbanemönstret som ger både utmärkt dragkraft och stabilitet.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Bulldozer • Väghyvlare • Hjullastare
OTR: Bulldozer • Väghyvlare • Hjullastare

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 14.00 R 24 |
| LI/SS | 153 A8/175 A2 |

Dimensions International Standard

| | |
|----------------------------|--------------------|
| Overall Width (mm) | 366 |
| Overall Diameter (mm) | 1370 |
| Static Loaded Radius (mm) | 625 |
| Rolling Circumference (mm) | 4141 |
| Rim Rec | 8.00 TG |
| Rim Alt | 9.00 GR , 10.00 VA |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (Kg)

| km/h / bar | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 3.25 | 3.50 | 3.75 | 5.25 | 5.50 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 40 | 2240 | 2430 | 2650 | 2800 | 3000 | 3250 | 3350 | 3650 | - | - |
| 10 | - | - | - | - | - | - | - | - | 6700 | 6900 |

Printed on 4/27/2024 12:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..