

EARTHMAX SR 23 - Tekniska specifikationer



Description

EARTHMAX SR 23 (G-2/L-2) är ett stålradialdäck för väghyvlar och hjullastare. Det har överlägsen dragkraft i både längs- och sidled och utmärkta självrensande egenskaper. Det tåliga höljet och slitbanemönstret med extra hög motståndskraft mot skärskador ger däckets en lång livslängd.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Väghyvlare • Hjullastare

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 15.5 R 25 |
| LI/SS | 146 A8/169 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 383 |
| Overall Diameter (mm) | 1264 |
| Static Loaded Radius (mm) | 559 |
| Rolling Circumference (mm) | 3756 |
| Rim Rec | 12.00/1.3 |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (Kg)

| km/h / bar | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 40 | 1550 | 1750 | 2000 | 2180 | 2360 | 2575 | 2800 | 3000 | - | - | - | - | - |
| 10 | - | - | - | - | - | - | - | - | 5000 | 5150 | 5450 | 5600 | 5800 |

Printed on 4/25/2024 8:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..