

EARTHMAX SR 25 PLUS - Tekniska specifikationer



Description

EARTHMAX SR 25 PLUS (G-2/L-2) är ett stålradialdäck särskilt avsett för väghyvlar och hjullastare som används under tuffa förhållanden vid vägbyggen och i gruvor. Det symmetriska slitbanemönstret har utmärkta självrensande egenskaper och ger utmärkt dragkraft och stabilitet vid terrängkörning.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Bulldozer • Väghyvlare • Hjullastare
OTR: Bulldozer • Väghyvlare • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	153 A8/175 A2

Dimensions International Standard

Overall Width (mm)	359
Overall Diameter (mm)	1372
Static Loaded Radius (mm)	626
Rolling Circumference (mm)	4146
Rim Rec	8.00TG
Rim Alt	9.00GR
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	5.25	5.50
40	2240	2430	2650	2800	3000	3250	3350	3650	-	-
10	-	-	-	-	-	-	-	-	6700	6900

Printed on 4/23/2024 6:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..