

## EARTHMAX SR 30 - Tekniska specifikationer



### Description

EARTHMAX SR 30 (E-3/L-3) är ett stålradialdäck för hjullastare och midjestyrd dumprar. Flera lager stålbälten och ett styvt blockmönster ger däck utmärkt dragkraft, stabilitet och hållbarhet. Gummiblandningen är extra motståndskraftig mot skärskador och gör EARTHMAX SR 30 till en idealisk lösning i en mängd olika tuffa miljöer.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/176 A2

## Dimensions US Standard

Usa code	94029112
TMPH	103
Overall Width (inch)	17.6
Overall Diameter (inch)	53
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	158.3
Rim Rec	14.00/1.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	9650	10200	10500	11000	11400	12000
5	13200	13600	14300	14800	15700	-

Printed on 4/17/2024 9:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..