

EARTHMAX SR 30 - Tekniska specifikationer



Description

EARTHMAX SR 30 (E-3/L-3) är ett stålradialdäck för hjullastare och midjestydda dumprar. Flera lager stålbälten och ett styvt blockmönster ger däckets utmärkt dragkraft, stabilitet och hållbarhet. Gummiblandningen är extra motståndskraftig mot skärskador och gör EARTHMAX SR 30 till en idealisk lösning i en mängd olika tuffa miljöer.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions US Standard

Usa code	94054442
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L3

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	28300	29100	30900	32000	33100

Printed on 4/15/2024 11:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..