

EARTHMAX SR 313 - Ladda ned faktablad



Description

EARTHMAX SR 313 är ett radialdäck helt i stål som designats för ramstyrda dumprar och hjullastare som används i hårda och steniga miljöer. Gummiblandningen ger bra skärmotstånd och det speciella däcktjänstret skyddar mot punkteringar och skador och har självrensande egenskaper. Däckskuldrans fyrkantiga design maximerar kontaktytan mot marken för utmärkt manövrerbarhet. Radialdäckkonstruktionen helt i stål består av stålbalten med flera lager av stål för extra lång hållbarhet. EARTHMAX SR 313 är det idealiska däck för verksamheter som kräver lastning och transporter.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Ramstyrd dumper (ADT) • Hjullastare

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | TMPH |
|--------------|---------------------------|----------|----------|--------|-----------------|-----------|---------|------|------|------|-------|------|------|
| 15.5 R 25 | CUT RESISTANT COMPOUND | 94066964 | E3/L3 | **/* | 160 B/169 A2 | 12.00/1.3 | | 15.5 | 49.8 | 22.3 | 150.5 | TL | 92 |

Printed on 4/25/2024 10:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..