

EARTHMAX SR 33 PLUS - Tekniska specifikationer



Description

EARTHMAX SR 33 PLUS är ett radialdäck med multiblockmönster som har konstruerats och designats särskilt för att ge enastående flyt- och dragförmåga på mjuka, sandiga, leriga och hårt packade underlag. Den kraftfulla stålradialstommen med stålbalten ger utmärkt hållbarhet och motståndskraft mot revor och punkteringar. EARTHMAX SR 33 PLUS besitter imponerande självrensande egenskaper och erbjuder överlägsen stabilitet.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	16.00 R 20
LI/SS	173/170 G

Dimensions US Standard

Usa code	94064038
Overall Width (inch)	17.6
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	156.5
Rim Rec	11.25
Rim Alt	10.00W, 10.0
ECE	E11-54R-0017916

Load capacity (lbs)

mph / psi	110
56	14330

Printed on 4/27/2024 9:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..