

EARTHMAX SR 33 - Tekniska specifikationer



Description

Earthmax SR 33 är ett radialdäck för lastbilar med flera användningsområden. Däckets multiblockmönster är utformat för att ge utomordentlig dragkraft på mjuka, sandiga eller leriga underlag. Earthmax SR 33 har utomordentlig stabilitet och bästa möjliga självrensande egenskaper. Det kraftiga stålförstärkta höljet är mycket pålitligt och tåligt mot revor och punkteringar.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Universalfordon

Version	STANDARD
Type	TL
Tyre Size	14.00 R 20
LI/SS	164/160 J

Dimensions US Standard

Usa code	94057757
Overall Width (inch)	15.4
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	151.2
Rim Rec	10.0
Rim Alt	9.0, 10.00W
ECE	E11-54R-0016678

Load capacity (lbs)

mph / psi	110
62 LS	11000
62 LD	9900

Printed on 4/27/2024 7:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..