

EARTHMAX SR 33 - Ladda ned faktablad



Description

Earthmax SR 33 är ett radialdäck för lastbilar med flera användningsområden. Däckets multiblockmönster är utformat för att ge utomordentlig dragkraft på mjuka, sandiga eller leriga underlag. Earthmax SR 33 har utomordentlig stabilitet och bästa möjliga självrensande egenskaper. Det kraftiga stålförstärkta höljet är mycket pålitligt och tåligt mot revor och punkteringar.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Universalfordon

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
14.00 R 20	STANDARD	94057757	164/160 J	10.0	9.0, 10.00W	15.4	49.2	22.7	151.2	TL	E11-54R-0016678
335/80 R 20	STANDARD	94059478	150 K	11		13.2	41.2	18.3	123.8	TL	E11-54R-0016679
365/80 R 20 (14.5 R 20)	STANDARD	94061907	152 K	11		14.2	43.1	19.5	130.6	TL	E11-54R-0017314
395/85 R 20	STANDARD	94050611	168 J	10.00W	10.00HF	15.5	46.6	21.2	141.3	TL	E11-54R-0017315

Printed on 4/24/2024 9:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..