

EARTHMAX SR 34 - Tekniska specifikationer



Description

EARTHMAX SR 34 är ett radialdäck helt i stål speciellt utformat för dumpers som används för bland annat gruvdrift, stenbrott, skogsavverkning och transport. Det oriktade däckmönster ger utmärkt dragförmåga och stabilitet i alla typer av terräng. EARTHMAX SR 34 är idealiskt för hantering av tunga laster. Den robusta stålradialstommen ger utmärkt motståndskraft mot slitage, revor och punkteringar. Den förstärkta vulsten och specifika skulderdesig bidrar till däckets långa livscykel, även under de mest krävande arbetsförhållandena.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Stel dumper

Version	ULTRA CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	183 B

Dimensions International Standard

Overall Width (mm)	440
Overall Diameter (mm)	1508
Static Loaded Radius (mm)	693
Rolling Circumference (mm)	4575
Rim Rec	11.25/2.0
Star Rating	***
TRA Code	E3+
Tread Depth	36

Load capacity (Kg)

km/h / bar	7.50	8.00	8.50	9.00
50	7500	8000	8250	8750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 5:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..