

EARTHMAX SR 35 - Ladda ned faktablad



Description

Earthmax SR 35 är ett stålradialdäck med låg profil, avsett för midjestyrd dumprar och hjullastare. Earthmax SR 35 har både utmärkt dragkraft och stabilitet. Det kraftiga stålbelagda höljet är utomordentligt pålitligt och tåligt mot revor och punkteringar. Däcket finns tillgängligt med en skärtålig gummiblandning som ger en mycket lång livslängd även under svåra förhållanden.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | TMPH |
|-----------------------------------|---------------------------|----------|----------|--------|-----------------|------------|--------------------------|------|------|------|-------|------|------|
| 650/65 R 25 (25/65 R 25) | CUT RESISTANT COMPOUND | 94058587 | E3 | ** | 180 B | 19.50/2.5 | | 25 | 59 | 26.3 | 176.9 | TL | 138 |
| 650/65 R 25 (25/65 R 25) | CUT RESISTANT COMPOUND | 94058631 | E3/L3 | **/* | 180 B/193 A2 | 19.50/2.5 | | 25 | 59 | 26.3 | 176.9 | TL | 138 |
| 650/65 R 25 (25/65 R 25) | CUT RESISTANT COMPOUND | 94058624 | L3 | * | 193 A2 | 19.50/2.5 | | 25 | 59 | 26.3 | 176.9 | TL | 0 |
| 750/65 R 25 (30/65 R 25) | CUT RESISTANT COMPOUND | 94051786 | E3 | ** | 190 B | 24.00/3.0 | 22.00/3.0,25.00/3.0 | 29.1 | 63 | 28.1 | 189.1 | TL | 153 |
| 750/65 R 25 (30/65 R 25) | CUT RESISTANT COMPOUND | 94053636 | E3/L3 | **/* | 190 B/202 A2 | 24.00/3.0 | 22.00/3.0 ; 25.00/3.0 | 29.1 | 63 | 28.1 | 189.1 | TL | 153 |
| 750/65 R 25 (30/65 R 25) | CUT RESISTANT COMPOUND | 94071340 | L3 | ** | 209 A2 | 24.00/3.0 | 22.00/3.0,25.00/3.0 | 29.1 | 63 | 28.1 | 189.1 | TL | 0 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94064410 | E3/L3 | **/* | 195 B/206 A2 | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 151 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94064427 | E3 | ** | 195 B | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 151 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94064434 | L3 | * | 206 A2 | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 0 |
| 775/65 R 29 | CUT RESISTANT COMPOUND | 94067589 | L3 | ** | 213 A2 | 24.00/3.5 | 24.00/3.0, 25.00/3.5 | 30.5 | 69 | 31 | 209.1 | TL | 0 |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | 94059812 | E3/L3 | **/* | 203 B/214 A2 | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 35 | 73.2 | 32.1 | 218.9 | TL | 191 |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | 94059805 | E3 | ** | 203 B | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 35 | 73.2 | 32.1 | 218.9 | TL | 191 |
| 875/65 R 29 (35/65 R 29) | CUT RESISTANT COMPOUND | 94059836 | L3 | * | 214 A2 | 27.00/3.50 | 27.00/3.0, 28.00/3.5 | 35 | 73.2 | 32.1 | 218.9 | TL | 0 |

Printed on 4/29/2024 7:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..