

EARTHMAX SR 412 - Tekniska specifikationer



Description

EARTHMAX SR 412 (E-4/L-4) är ett radialdäck helt i stål som konstruerats och designats för ramstyrda dumprar, lastare och schaktmaskiner. Dess starka stålradialstomme och däckbälten gör att EARTHMAX SR 412 klarar högre belastningar med bibehållen utmärkt stabilitet och motverkar dessutom skador från snitt, ihakningar och punkteringar.

Det garanterar utmärkt grepp och exceptionell dragförmåga mot värme tack vare sitt unika E-4-slitbanemönster.

EARTHMAX SR 412 har utvecklats med en kvadratisk axel som maximerar markkontakten för utmärkt manövrerbarhet.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Ramstyrd dumper (ADT) • Bulldozer • Hjullastare

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	750/65 R 25 (30/65 R 25)
LI/SS	190 B

Dimensions US Standard

Usa code	94064144
TMPH	157
Overall Width (inch)	30.7
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	190.5
Rim Rec	24.00/3.0
Rim Alt	22.00/3.0; 25.00/3.0
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	58	62	65	69
30	20900	21500	22700	23400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/9/2024 4:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..