

EARTHMAX SR 41 - Tekniska specifikationer



Description

EARTHMAX SR 41 (E-4/L-4) är ett radialdäck helt i stål perfekt för ramstyrda dumprar, lastare och schaktmaskiner. Tack vare strukturen helt i stål och ett speciellt blockmönster ger EARTHMAX SR 41 utmärkt motståndskraft mot punkteringar och längre livslängd. EARTHMAX SR 41 är även tillgängligt i E4**** för dumpers med lågprofil (LPDT) som används i underjordisk drift.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Ramstyrd dumper (ADT), Bulldozer, Hjullastare, Dumper med lågprofil

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	35/65 R 33

Dimensions US Standard

Usa code	94069415
Overall Width (inch)	35.3
Overall Diameter (inch)	81.2
Static Loaded Radius (inch)	36.5
Rolling Circumference (inch)	247.4
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****
TRA Code	E4

Load capacity (lbs)

mph / psi

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..