



EARTHMAX SR 423 - Tekniska specifikationer



Description

EARTHMAX SR 423 är ett radialdäck helt i stål som lämpar sig för en rad olika tillämpningar, bland annat gruvdrift, transport och skogsbruk. Det oriktade mönstret ger utmärkt dragförmåga och stabilitet i all möjlig terräng. Däcket är idealiskt för hantering av tunga laster. Den robusta stålradialstommen ger imponerande motståndskraft mot slitage, revor och punkteringar. Den förstärkta vulsten och skulderdesignen bidrar till däckets långa livslängd, även under krävande arbetsförhållanden.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Väg- och terränggående lastbil

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	149/146 J

Dimensions US Standard

Usa code	94060481
Ply Rating	18
Overall Width (inch)	10.6
Overall Diameter (inch)	41.9
Rim Rec	7.50
Rim Alt	8.00
Tread Depth	25

Load capacity (lbs)

mph / psi	120
62 Load Single	7165
62 Load Dual	6615

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 12:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..