EARTHMAX SR 42 - Tekniska specifikationer

Description

EARTHMAX SR 42 är ett terrängradialdäck som är specialkonstruerat för gruvtransporter och tillämpningar inom skogsavverkning. Den distinkta mönsterdesignen ger enastående dragförmåga och stabilitet i sidled och bra broms- och kurvtagningsegenskaper i hård terräng och på grus, till och med på is och snö. Den speciella skär- och slittåliga gummiblandningen är faktiskt särskilt lämplig i klimat med extrem kyla. EARTHMAX SR 42 har en stålradialstomme som ger utmärkt hållbarhet och lång livslängd.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Gruvtransport

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 25
LI/SS	171 B

Dimensions US Standard

Usa code	94048984
TMPH	72
Overall Width (inch)	15
Overall Diameter (inch)	55.6
Static Loaded Radius (inch)	25.7
Rolling Circumference (inch)	166.6
Rim Rec	10.00/1.5
Rim Alt	--
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	102	116
30	12800	13600

Printed on 4/26/2024 7:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..