

## EARTHMAX SR 431 - Tekniska specifikationer



### Description

EARTHMAX SR 431 (E-4) är ett däck helt i stål, specialdesignat för anläggningsbilar som körs i krävande gruvmiljöer (dagbrott och underjordiska gruvor). Det oriktade mönstret säkerställer utmärkt dragförmåga och stabilitet i all möjlig terräng. Däcket har ett starkt hölje helt i stål och en speciell gummiblandning som gör det utomordentligt skär- och punkteringsbeständigt, med lång hållbarhet även i steniga, slitiga och krävande miljöer.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 25
LI/SS	185 B

## Dimensions International Standard

TKPH	140
Overall Width (mm)	520
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	760
Rolling Circumference (mm)	5040
Rim Rec	13.00/2.5
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	7300	7500	7750	8000	8250	8500	8750	9000	9250

Printed on 4/26/2024 7:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..