

EARTHMAX SR 431 - Ladda ned faktablad



Description

EARTHMAX SR 431 (E-4) är ett däck helt i stål, specialdesignat för anläggningsbilar som körs i krävande gruvmiljöer (dagbrott och underjordiska gruvor). Det oriktade mönstret säkerställer utmärkt dragförmåga och stabilitet i all möjlig terräng. Däcket har ett starkt hölje helt i stål och en speciell gummiblandning som gör det utomordentligt skär- och punkteringsbeständigt, med lång hållbarhet även i steniga, slitiga och krävande miljöer.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Stel dumper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
16.00 R 25	CUT RESISTANT COMPOUND	E4	**	177 B	11.25/2.0		452	1532	713	4649	TL	166
18.00 R 25	CUT RESISTANT COMPOUND	E4	**	185 B	13.00/2.5		520	1660	760	5040	TL	140
18.00 R 25	CUT RESISTANT COMPOUND (UMS)	E4	****		13.00/2.5		520	1660	760	5040	TL	

Printed on 4/26/2024 5:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..